

GV Model Name	GV F/W Number	Maximum throughput	Note			
GV-ABL2701	A02-GV-ABL2701_V1.01_2018-07-03	40Mbps	1. If the throughput of the camera is within 40Mbps, the maximum number of live views is 20. (e.g., NVR, VMS, etc.) 2. If the throughput of the camera is within 40Mbps, the maximum number of web interface connections is 32.			
GV-ADR2701						
GV-ADR2702	A02-GV-ADR2702_V1.03_2021_04_13	40Mbps	1. If the throughput of the camera is within 40Mbps, the maximum number of live views is 20. (e.g., NVR, VMS, etc.) 2. If the throughput of the camera is within 40Mbps, the maximum number of web interface connections is 32.			
GV-ADR4702						
GV-ABL2703						
GV-ABL4703						
GV-TDR2702						
GV-TDR4702						
GV-TBL2703						
GV-TBL4703						
GV-TVD4700						
GV-TBL4700						
GV-TDR2700						
GV-EBD2702				A02-GV-EBD2702_V1.05_2021_04_13	40Mbps	1. If the throughput of the camera is within 40Mbps, the maximum number of live views is 20. (e.g., NVR, VMS, etc.) 2. If the throughput of the camera is within 40Mbps, the maximum number of web interface connections is 32.
GV-ABL2702						
GV-AVD2700						
GV-TDR4700	A02-GV-EBD4700_V1.08_2021_04_13	40Mbps	1. If the throughput of the camera is within 40Mbps, the maximum number of live views is 20. (e.g., NVR, VMS, etc.) 2. If the throughput of the camera is within 40Mbps, the maximum number of web interface connections is 32.			
GV-ADR4701						
GV-ABL4701						
GV-EBD4700						
GV-EBD4711						
GV-ABL4712	A02-GV-ABL4712_V1.05_2021_04_13	30Mbps	1. If the throughput of the camera is within 30Mbps, the maximum number of live views is 20. (e.g., NVR, VMS, etc.) 2. If the throughput of the camera is within 40Mbps, the maximum number of web interface connections is 32.			
GV-AVD4710						
GV-TBL4710						
GV-TVD4710						
GV-EBD8700	A02-GV-EBD8700_V1.03_2021_04_13	40Mbps	1. If the throughput of the camera is within 40Mbps, the maximum number of live views is 20. (e.g., NVR, VMS, etc.) 2. If the throughput of the camera is within 40Mbps, the maximum number of web interface connections is 32.			
GV-EBD8711	A02-GV-ABL8712_V1.04_2021_04_13	40Mbps	1. If the throughput of the camera is within 40Mbps, the maximum number of live views is 20. (e.g., NVR, VMS, etc.) 2. If the throughput of the camera is within 40Mbps, the maximum number of web interface connections is 32.			
GV-ABL8712						
GV-AVD8710						
GV-TBL8710						
GV-TVD8710						
GV-SD3732-IR	A02-GV-SD3732-IR_V1.04_2021_04_13	40Mbps	1. If the throughput of the camera is within 40Mbps, the maximum number of live views is 20. (e.g., NVR, VMS, etc.) 2. If the throughput of the camera is within 40Mbps, the maximum number of web interface connections is 32.			
GV-SD2722-IR						
GV-TBL4711	A02-GV-TBL4711_V1.02_2021_04_08	40Mbps	1. If the throughput of the camera is within 40Mbps, the maximum number of live views is 20. (e.g., NVR, VMS, etc.) 2. If the throughput of the camera is within 40Mbps, the maximum number of web interface connections is 32.			
GV-TVD4711						
GV-TDR4703						
GV-EBD4701						
GV-EBD4712						
GV-TFD4700						
GV-TBL8810	A02-GV-TBL8810_V1.02_2021_08_10	40Mbps	1. If the throughput of the camera is within 40Mbps, the maximum number of live views is 20. (e.g., NVR, VMS, etc.) 2. If the throughput of the camera is within 40Mbps, the maximum number of web interface connections is 32.			
GV-TVD8810						
GV-TBL8804						
GV-EBD8800						
GV-EBD8813						
GV-FER5702 (For v1.03 or above only)						
GV-TDR2704	A02-GV-TDR2704_V1.00_2021_06_29	40Mbps	1. If the throughput of the camera is within 40Mbps, the maximum number of live views is 6. (e.g., NVR, VMS, etc.) 2. If the throughput of the camera is within 40Mbps, the maximum number of web interface connections is 32.			
GV-EBD2704						
GV-TBL2705						
GV-TDR4704	A02-GV-TDR4704_V1.01_2021-08-20	40Mbps	1. If the throughput of the camera is within 40Mbps, the maximum number of live views is 6. (e.g., NVR, VMS, etc.) 2. If the throughput of the camera is within 40Mbps, the maximum number of web interface connections is 32.			
GV-TBL4705						
GV-EBD4704						
GV-TDR4803						
GV-TBL4810						
GV-TVD4810						
GV-EBD4813						
GV-BLFC5800						
GV-SD4834-IR				A02-GV-SD4834-IR_V1.00_2021_11_18	40Mbps	1. If the throughput of the camera is within 40Mbps, the maximum number of live views is 20. (e.g., NVR, VMS, etc.) 2. If the throughput of the camera is within 40Mbps, the maximum number of web interface connections is 32.
GV-SD4825-IR						
GV-PTZ5810-IR	A02-GV-PTZ5810-IR_V1.00_2021-12-10	40Mbps	1. If the throughput of the camera is within 40Mbps, the maximum number of live views is 20. (e.g., NVR, VMS, etc.) 2. If the throughput of the camera is within 40Mbps, the maximum number of web interface connections is 32.			