

**Comparison Chart for GV-I/O Box 4Port V1.0, V1.1 and V1.2**

Model		GV-IO Box 4Port		
H/W Version		V1.0	V1.1	V1.2
H/W Chipset		<b>旺玖 Exar</b>		
OS Supported	32-bit	Windows XP / Vista / 7 / Server 2008		
	64-bit	Windows 7 / Server 2008 R2		
Compatible S/W		GV-System version 8.2 or above		
Connections to PC		<b>RJ-11 to USB RJ-11 to DB9 RS-485</b>		<b>USB Type A to B RS-485</b>
Input	Input	4		
	Input Signal	Dry Contact Wet Contact, 9-30V AC/DC		
Communication	Relay Output	4		
	Relay Status	Normal open		
	Relay Capacitance	30 VDC, 3A		
	USB Connection	125 / 250 VAC, 3A		
	RS-232 / RS-485 Connection	30 VDC, 3A		
DC IN		DC 12V, 1A		
Address		0-9, A-F		
Terminal Resistance		120 ohm		
Environmental Conditions		0 ~ 50 °C / 32 ~ 122 °F 5% ~ 95% (non-condensing)		
Dimensions (W x H x D)		111.4 x 27.5 x 101 (mm) / 4.39 x 1.08 x 3.98 (in)		

\*Server 2008R2 及 Server 2012 只有 64bit 的 O.S.